

CAPTAIN

EU MODEL 263 (25 HP)



THE **ROAR** GETS **LOUDER**
FROM THE **LAND** OF **LIONS**

MID ROPS

Orchard Special

1st*
Company to offer
MID ROPS in 25 HP Tractors

Powered by
mitsubishi
DIESEL ENGINE

STAGE V



CAPTAIN
AGRI MACHINERY

8G
THE EIGHTH
GENERATION

Note : Products undergo continuous upgradations.

*MADE IN INDIA

www.captainagri.com

EU-ENGLISH

CAPTAIN

EU MODEL 263 - STAGE V


MID ROPS



Italian
Designed
Lion Face



Hydrostatic
Power
Steering




Engine : Stage V
Mitsubishi
3 Cylinder



Gear levers
on the
Side




Front
Opening
Bonnet



Ergonomic
Seating &
Footboard Area



850 kg
Hyd. Lifting
Capacity




2 PTO
Speeds



Differential
Lock



Multi Disc
Oil Immersed
Brakes



Smart
ADDC (2 Lever)
Hydraulics

Narrow Track
Option Separately Available in this Model

SPECIFICATIONS

CAPTAIN 263 4WD
Agriculture

CAPTAIN 263 4WD
Turf

CAPTAIN 263 4WD
Industrial / Flotation

CAPTAIN 263 4WD
Agricultural Wide Plus

CAPTAIN 263 4WD
Agrimax Turf RT 333 Garden

CAPTAIN 263 4WD
Wider F-Agri

CAPTAIN 263 4WD
Industrial (Regular)

CAPTAIN 263 4WD
Basic - Agri

Engine Horse Power Ps (kW)
Engine Type
No. of Cylinder
Capacity (CC)
Rated Speed (RPM)
Cooling System
Bore / Stroke (mm)
Max Torque (Nm) @ RPM

Tyres

Transmission

Hyd.

Dimensions*

	25 (18.2)							
	Mitsubishi MVS3L2 - Stage - V							
	3							
	1319							
	2500							
	Liquid Cooled							
	78/92							
	76.3 (Nm) @ 2000 RPM							
Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	180/85D12	240/60R12	23 x 8.5 - 12	23 x 8.5 - 12	5.00 x 12
Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R20	320/65R18	280/70R18	12 x 16.5	8.00 x 18
Type	Sliding Mesh Transmission : Side Shift Gear Levers							
Gears	9 Forward, 3 Reverse							
Max. Speed Rounded off (km/hr.)	20	18	19	20	19	18	19	18
PTO RPM	540 & 540 E							
Steering	Hydrostatic Power Steering							
Brake Type	Multi Disc Oil Immersed							
Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)							
Lift Capacity (kgs.)	850 (at Lower Link Point)							
No. of Pumps	2 (One for Hydrostatic Steering & Other for Hydraulic System)							
Auxiliary Hydraulics	1 DA Auxiliary Hydraulics with 2 QRCs							
Length x Width (mm)	2700* x 1080	2700* x 1390	2700* x 1390	2700* x 1167	2700* x 1220	2700* x 1220	2700* x 1264	2700* x 1050
Height - with Front ROPS UP (mm)	2190	2140	2140	2185	2170	2150	2140	2150
Height - with Front ROPS Folded Down (mm)	1474	1424	1424	1469	1454	1434	1424	1434
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	1008	1050	1078	1039	1039	1014	1052	987

*Dimensions are with Standard Lower Links, it may vary with longer linkages.

#+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.

CAPTAIN AGRI MACHINERY EXIM LLP
Exports Arm of **CAPTAIN TRACTORS PVT. LTD.**

Veraval (Shapar), District : Rajkot (Gujarat) INDIA. Pincode - 360024.
Ph./Landline : + 91 281 299 4386, Mo : +91 99250 40445, Email : exports@captaintractors.com

Follow us on

*MADE IN INDIA

www.captainagri.com