


# CAPTAIN *UTILITY SERIES*

**4533** **2WD**



Powerful 3 Cylinder Engine



Constant + Sliding Mesh Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic

Also Available in **4WD**

## Technical Specification

<b>ENGINE</b>	<b>Kirloskar</b>
Model	3R 1040 NA1
Power (HP) Category	45 Hp
Type	4 Stroke Liquid Cooled Diesel Engine
No. of Cylinder	3
Bore/Stroke (cm)	105/120
Cubic Capacity	3120
Rated Engine Speed	2000
Torque	188 Nm / 20% Backup Torque
Air Cleaner	Dry Type
<b>CLUTCH</b>	
Type	Dual Clutch
Plate Size	280 mm
<b>TRANSMISSION</b>	<b>Captain</b>
Type	Constant Mesh with Collar Shift
Gears	8F + 2R
Speed	Min 3.08 Km/hr, Max 30.41 Km/hr
<b>PTO</b>	
PTO Speed	540@1765
PTO Type	Live PTO
No. of Splines	6
<b>BRAKES</b>	
Brakes	Oil Immersed Multi Disc
Parking Brake	Mechanical
<b>STEERING</b>	
Steering Type	Hydrostatic Power Steering
<b>HYDRAULICS</b>	
Hyd. Pump Type	TANDEM
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	2100
3 Point Linkage	CAT-1 / CAT-2



*Front Bumper is standard supply.  
(ROPS and Sun Roof Canopy is Optional)*

ELECTRICAL INSTRUMENTS	
Battery , Capacity	88 Ah
Alternator	36A
Starter Motor	2.3 kW
TYRES	
Front	6.00x16
Rear	14.9x28
FUEL TANK	
Capacity	52 Ltr.
DIMENSIONS	
Front Track Width With Front Bumper	1369 mm
Rear Track Width	1420 mm
Tractor Length	3771 mm
Tractor Width	1805 mm
Tractor Height with Canopy	2427 mm
Wheel Base	2151 mm
Min. Ground Clearance	450 mm
Min. Turning Radius	R-7.09 m, L-7.14 m
Weight of Tractor With ROPS	2210 Kg

Note : All Specifications are subject to change without prior notice. Utility Series is available only for exports.