


CAPTAIN *UTILITY SERIES*

4533 4WD



Powerful 3 Cylinder Engine



Constant + Sliding Mesh Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic

Also Available in **2WD**

Technical Specification

ENGINE	Kirloskar
Model	3R 1040 NA1
Power (HP) Category	45 Hp
Type	4 Stroke Liquid Cooled Diesel Engine
No. of Cylinder	3
Bore/Stroke (cm)	105/120
Cubic Capacity	3120
Rated Engine Speed	2000
Torque	188 Nm / 20% Backup Torque
Air Cleaner	Dry Type
CLUTCH	
Type	Double Clutch
Plate Size	280 mm
TRANSMISSION	Captain
Type	Constant Mesh with Collar Shift
Gears	8F + 2R
Speed	Min 3.08 Km/hr, Max 29.24 Km/hr
PTO	
Type	Live PTO
PTO Speed	540@1765
No. of Splines	6
BRAKES	
Brakes	Oil Immersed Multi Disc
Parking Brake	Mechanical
STEERING	
Steering Type	Hydrostatic Power Steering
HYDRAULICS	
Hyd. Pump Type	TANDEM PUMP
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	2100
3 Point Linkage	CAT-1 / CAT-2



Front Weight with Platform is standard supply.
(ROPS and Sun Roof Canopy is Optional)

ELECTRICAL INSTRUMENTS	
Battery , Capacity	88 Ah
Alternator	36A
Starter Motor	2.3 kW
TYRES	
Front	9.50x24
Rear	14.9x28
FUEL TANK	
Capacity	52 Ltr.
DIMENSIONS	
Front Track Width	1334 mm
Rear Track Width	1420 mm
Tractor Length With Front Weight	3836 mm
Tractor Width	1805 mm
Tractor Height with Canopy	2427 mm
Wheel Base	2216 mm
Min. Ground Clearance	400 mm
Min. Turning Radius	R-7.09 m, L-7.14 m
Weight of Tractor With ROPS	2330 Kg

Note : All Specifications are subject to change without prior notice. Utility Series is available only for exports.