


# CAPTAIN *UTILITY SERIES*

## 4535 4WD



Powerful 3 Cylinder Engine



Collar Shift+Synchro Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic

Also Available in **2WD**

## Technical Specification

<b>ENGINE</b>	<b>Kirloskar</b>
Model	3R 1040 NA1
Power (HP) Category	45 Hp
Type	4 Stroke Water Cooled Diesel Engine
No. of Cylinder	3
Bore/Stroke (cm)	105/120
Cubic Capacity	3120
Rated Engine Speed	2000
Torque	188 Nm / 20% Backup Torque
Air Cleaner	Dry Type
<b>CLUTCH</b>	
Type	Dual Clutch
Plate Size	280 mm
<b>TRANSMISSION</b>	<b>Carraro</b>
Type	Constant Mesh with Collar Shift
Gears	8F + 8R
Speed	Min 2.95 Km/hr, Max 33.44 Km/hr
<b>PTO</b>	
Type	Independent
PTO Speed	540 & 540 E
No. of Splines	6
<b>BRAKES</b>	
Brakes	Oil Immersed Multi Disc
Parking Brake	Mechanical
<b>STEERING</b>	
Steering Type	Hydrostatic Power Steering
<b>HYDRAULICS</b>	
Hyd. Pump Type	TANDEM PUMP
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	1200
3 Point Linkage	CAT-1 / CAT-2



*Front Weight with Platform, ROPS and Sun Roof Canopy is standard supply.*

ELECTRICAL INSTRUMENTS	
Battery , Capacity	88 Ah
Alternator	36A
Starter Motor	2.3 kW
TYRES	
Front	8.00x18
Rear	13.6x28
FUEL TANK	
Capacity	52 Ltr.
DIMENSIONS	
Front Track Width	1369 mm
Rear Track Width	1425 mm
Tractor Length With Front Weight	3670 mm
Tractor Width	1695 mm
Tractor Height With Canopy	2300 mm
Wheel Base	2010 mm
Min. Ground Clearance	400 mm
Min. Turning Radius	R-7.2 m, L-7.3 m
Weight of Tractor With ROPS	2390 Kg

Note : All Specifications are subject to change without prior notice. Utility Series is available only for exports.