


CAPTAIN *UTILITY SERIES*

5033 4WD



Powerful 3 Cylinder Engine



Constant + Sliding Mesh Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic

Also Available in **2WD**

Technical Specification

ENGINE	
Model	Kirloskar 3R 1040
Power (HP) Category	50 Hp
Type	4 Stroke Water Cooled Diesel Engine
No. of Cylinder	3
Bore/Stroke (cm)	105/120
Cubic Capacity	3120
Rated Engine Speed	2200
Torque	188 Nm / 20% Backup Torque
Air Cleaner	Dry Type
CLUTCH	
Type	Dual Clutch
Plate Size	280 mm
TRANSMISSION	
Type	Constant Mesh with Collar Shift
Gears	8F + 2R
Speed	Min 3.08 Km/hr, Max 30.41 Km/hr
PTO	
PTO Speed	Live PTO
PTO Options	540 @1765
No. of Splines	6
BRAKES	
Brakes	Oil Immersed Multi Disc
Parking Brake	Mechanical
STEERING	
Steering Type	Hydrostatic Power Steering
HYDRAULICS	
Hyd. Pump Type	TANDEM
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	2100
3 Point Linkage	CAT-1 & CAT-2



Front Weight with Platform,
ROPS and Sun Roof Canopy is standard supply.

ELECTRICAL INSTRUMENTS	
Battery , Capacity	88 Ah
Alternator	36A
Starter Motor	2.3 kW
TYRES	
Front	8.3x20
Rear	14.9x28
FUEL TANK	
Capacity	52 Ltr.
DIMENSIONS	
Front Track Width	1334 mm
Rear Track Width	1420 mm
Tractor Length With Front Weight	3800 mm
Tractor Width	1800 mm
Tractor Height with Canopy	2400 mm
Wheel Base	2216 mm
Min. Ground Clearance	400 mm
Min. Turning Radius	R-7.09 m, L-7.14 m
Weight of Tractor With ROPS	2290 Kg

Note : All Specifications are subject to change without prior notice. Utility Series is available only for exports.