


# CAPTAIN *UTILITY SERIES*

## 6045 4WD



Powerful 4 Cylinder Engine



Synchromesh Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic

Also Available in **2WD**

## Technical Specification

<b>ENGINE</b>		<b>Kirloskar</b>
Model	4R 1040	
Power (HP) Category	60 Hp	
Type	4 Stroke Water Cooled Diesel Engine	
No. of Cylinder	4	
Bore/Stroke (cm)	105/120	
Cubic Capacity	4160	
Rated Engine Speed	2200	
Torque	227 Nm / 18.2% Backup Torque	
Air Cleaner	Dry Type	
<b>CLUTCH</b>		
Type	Double Clutch	
Plate Size	280 mm (Primary)	
<b>TRANSMISSION</b>		
<b>Carraro</b>		
Type	Synchromesh F/R	
Gears	12F + 12R	
Speed	Min 1.72 Km/hr, Max 35.47 Km/hr	
<b>PTO</b>		
Type	Independent	
PTO Speed	540 & 540E	
No. of Splines	6	
<b>BRAKES</b>		
Brakes	Oil Immersed Multi Disc	
Parking Brake	Mechanical	
<b>STEERING</b>		
Steering Type	Hydrostatic Power Steering	
<b>HYDRAULICS</b>		
Hyd. Pump Type	TANDEM PUMP	
A. Position	To Hold The Lower Link At Any Desired Height	
B. Automatic Depth Draft Control	Maintains Uniform Draft	
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.	
Lifting Capacity (Kg)	2200	
Auxiliary Hydraulics	1 DA with 2 QRCs Standard Supply	
3 Point Linkage	CAT-2	



*Front Weight with Platform, Rear Wheel Weight, ROPS and Sun Roof Canopy is standard supply.*

### ELECTRICAL INSTRUMENTS

Battery , Capacity	100 Ah
Alternator	55A
Starter Motor	2.7 kW

### TYRES

Front	9.50x24
Rear	16.9x28

### FUEL TANK

Capacity	58 Ltr.
----------	---------

### DIMENSIONS

Front Track Width	1508 mm
Rear Track Width	1491 mm
Tractor Length With Front Weight	4020 mm
Tractor Width	1920 mm
Tractor Height With Canopy	2635 mm
Wheel Base	2290 mm
Min. Ground Clearance	440 mm
Min. Turning Radius	R-8.2 m, L-8.3 m
Weight of Tractor With ROPS	2952 Kg

Note : All Specifications are subject to change without prior notice. Utility Series is available only for exports.