


CAPTAIN *UTILITY SERIES*

7290 **2WD**



Powerful 4 Cylinder Engine



Synchromesh Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic

Also Available in **4WD**

Technical Specification

ENGINE	
Model	Kirloskar 4R 1040 NA
Power (HP) Category	72 Hp
Type	4 Stroke Liquid Cooled Diesel Engine
No. of Cylinder	4
Bore/Stroke (cm)	105/120
Cubic Capacity	4160
Rated Engine Speed	2200
Torque	295 Nm / 18% Backup Torque
Air Cleaner	DryType
CLUTCH	
Type	Double Clutch
Plate Size	280 mm
TRANSMISSION	
Type	Carraro
Type	Synchromesh
Gears	12F + 12R
Speed	Min 1.87 Km/hr, Max 38.5 Km/hr
PTO	
Type	Independent
PTO Speed	540 & 540 E
No. of Splines	6
BRAKES	
Brakes	Wet Brake
Parking Brake	Mechanical
STEERING	
Steering Type	Hydrostatic Power Steering
HYDRAULICS	
Hyd. Pump Type	TANDEM PUMP
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	2200
3 Point Linkage	CAT-2



Front Weight with Platform, Rear Wheel Weight, ROPS and Sun Roof Canopy is standard supply.

ELECTRICAL INSTRUMENTS	
Battery , Capacity	100 Ah
Alternator	55A
Starter Motor	2.7 kW
TYRES	
Front	7.50x16
Rear	13.6x38
FUEL TANK	
Capacity	80 Ltr.
DIMENSIONS	
Front Track Width	1410 mm
Rear Track Width	1430 mm
Tractor Length With Front Weight	4200 mm
Tractor Width	1790 mm
Tractor Height With Canopy	2820 mm
Wheel Base	2350 mm
Min. Ground Clearance	425 mm
Min. Turning Radius	R-8.2 m, L-8.3 m
Weight of Tractor With ROPS	2950 Kg

Note : All Specifications are subject to change without prior notice. Utility Series is available only for exports.