


# CAPTAIN *UTILITY SERIES*

## 9045 4WD



Powerful 4 Cylinder Engine



Synchromesh Gear Box



Cost Efficient



Low Fuel Consumption



Powerful Hydraulic

*\*Cabin available optionally*

## Technical Specification

ENGINE	
Model	Kirloskar 4R 1040 TC
Power (HP) Category	90 Hp
Type	Turbo Charged 4 Stroke Liquid Cooled Diesel Engine
No. of Cylinder	4
Bore/Stroke (cm)	105/120
Cubic Capacity	4160
Rated Engine Speed	2200
Torque	361 Nm / 25% Backup Torque
Air Cleaner	Dry Type
CLUTCH	
Type	Dual Clutch
Plate Size	310 mm
TRANSMISSION	
Type	Carraro
Type	Synchromesh F/R
Gears	12F + 12R
Speed	Min 1.57 Km/hr, Max 32.31 Km/hr
PTO	
Type	Independent
PTO Speed	540 & 540E
No. of Splines	6
BRAKES	
Brakes	Oil Immersed Multi Disc
Parking Brake	Mechanical
STEERING	
Steering Type	Hydrostatic Power Steering
HYDRAULICS	
Hyd. Pump Type	TANDEM PUMP
A. Position	To Hold The Lower Link At Any Desired Height
B. Automatic Depth Draft Control	Maintains Uniform Draft
C. Mix Control	For Simultaneous Use of Position And Draft Control For Optimum Field Output.
Lifting Capacity (Kg)	2500
Auxiliary Hydraulics	2 DA with 4 QRCs Standard Supply
3 Point Linkage	CAT-2



*Front Weight with Platform, Rear Wheel Weight, ROPS and Sun Roof Canopy is standard supply.*

ELECTRICAL INSTRUMENTS	
Battery , Capacity	100 Ah
Alternator	55A
Starter Motor	2.7 kW
TYRES	
Front	12.4x24
Rear	18.4x30
FUEL TANK	
Capacity	80 Ltr.
DIMENSIONS	
Front Track Width	1508 mm
Rear Track Width	1535 mm
Tractor Length With Front Weight	4235 mm
Tractor Width	2000 mm
Tractor Height With Canopy	2750 mm
Wheel Base	2360 mm
Min. Ground Clearance	420 mm
Min. Turning Radius	R-11.3 m, L-11.6 m
Weight of Tractor With ROPS	3410 Kg

Note : All Specifications are subject to change without prior notice. Utility Series is available only for exports.